ZETOR COMPAX

COMPAX CL 20, COMPAX CL 26, COMPAX CL 26 PLUS









COMPAX

Tractors of the compax model series are universal, reliable, and compact machines. Thanks to easy handling and sufficient power, the new tractors are perfect for the maintenance of villages, company premises, sports grounds, light agricultural works as well as gardening. Quality construction and low operating costs make these machines the right choice.

ENGINE

The new tractors are powered by Mitsubishi-designed engines offering 18 to 25 HP. These reliable water-cooled engines have enough power for your everyday tasks and at the same time boasts of low fuel consumption. While the COMPAX CL 20 is equipped with a 3-cylinder engine, the COMPAX CL 26 and CL 26 PLUS models have a durable 4-cylinder engine under the bonnet. All the new models comply with the Stage V emission standards.

TRANSMISSION

There are two different types of gearboxes. COMPAX CL 20 and COMPAX CL 26 are equipped with a manual transmission offering 6/2 speeds and 540 & 540E rear PTO revolutions. Model COMPAX CL 26 PLUS has an 8/2 manual transmission with 540 & 850 rear PTO revolutions.

HYDRAULICS

The maximum lifting capacity of the rear three-point hitch can reach up to 7,5 kN depending on the model allowing you to work with a wide range of implements.

OTHERS

All models are produced in the open version. On request, the tractor can be equipped with a protective cab with FOPS and ROPS. The ergonomic layout of the controls makes working with the tractor easier and simpler and contributes to driver comfort. The power steering and 4WD allow the tractors to perform a wide range of work tasks. The COMPAX series is available with front loader versions.

MODEL	UNITS	COMPAX CL 20	COMPAX CL 26	COMPAX CL 26 PLUS				
		ENGINE						
Emission standard	• Stage V							
	kW	13,6		18,3				
Max. power (R120 / EHK 120)	HP	18,5		24				
Rated speed	rpm		2700					
No. of Cylinders / Valves		3/6	4/8					
Displacement	cm ³	900	1306					
Engine filling / Cooling system	•							
Fuel tank	I	18	25					
		TRANSMISSION						
Type / Shifting	•		Manual					
No. of Gears (F/R)	•	6/	2	8/2				
Max. Speed	km/h	18		18-22				
		РТО						
Туре	•							
Rear PTO revolutions	rpm	540/5	40E	540/850				
Rear PTO shaft grooves		6 splines						
		HYDRAULICS						
Pump type	•	Gear pump	Double-gear pump					
Gear Pump Capacity	l/min	14,85	21,6					
Rear Hydraulic remotes (Quickcouplers)	•	2 (1 pair)						
		THREE-POINT HITCH	н					
Category		CAT-1						
Max. Lift Capacity	kN	5		7,5				
Regulation		Position / Draft						
		OTHER SPECIFICATIO	N					
Priver protection			ROPS / protective cabin OPT					
teering Wheel		Fixed						
-pole power socket		Yes						
eacon		Yes						
ront ballast		Yes						
		UNDERCARRIAGE						
Prive system			4WD					
) Operating brakes		Dry dr		Wet disc				
litches		,	Drawbar					
		DIMENSIONS						
Max. Front Ballas	kg		60					
Max. Length / Width / Height	mm	2820 / 1097-1435 / 2306-2345	2870 / 115	0-1435 / 2075-2320				
nin. Ground Clearance	mm	210		230				
Vheelbase	mm	1420)	1520				
Max. technically permissible veight	kg	1078		1149				
		WHEELS						
Agricultural		5x12 8x18		6x12 8,3x20				
		8,3X20 23X8,5-12						
Grassland / Industrial	•	33x15,5-16,5						





FOLLOW US

- facebook.com/zetor
- twitter.com/zetortractors
- instagram.com/zetortractors
- youtube.com/traktoryzetor

THE PICTURES AND PHOTOGRAPHS USED ARE MERELY FOR ILLUSTRATION PURPOSES, AS THE PRODUCTS DEPICTED IN THIS CATALOGUE MAY SHOW ITEMS OF EQUIPMENT THAT ARE NOT AVAILABLE IN STANDARD MODELS AND MAY BE AVAILABLE AS OPTIONAL EXTRAS. ZETOR TRACTORS A.S. RESERVES THE RIGHT TO CHANGE THE DATA AND INFORMATION PUBLISHED IN THIS CATALOGUE WITHOUT PREVIOUS NOTIFICATION. ZETOR TRACTORS A.S. IS NOT LIABLE FOR ISSUES ARISING FROM ANY POTENTIALLY FAULTY INFORMATION PUBLISHED IN THIS CATALOGUE. THIS CATALOGUE WAS LAST REVIEWED ON: 11/2022

www.zetor.com zetor@zetor.com